

**RoGator RG900, RG1100, and
RG1300 SmarTrax™
Installation Manual**

P/N 016-4001-090 Rev B 04/16

E19896

Disclaimer

While every effort has been made to ensure the accuracy of this document, Raven Industries assumes no responsibility for omissions and errors. Nor is any liability assumed for damages resulting from the use of information contained herein.

Raven Industries shall not be responsible or liable for incidental or consequential damages or a loss of anticipated benefits or profits, work stoppage or loss, or impairment of data arising out of the use, or inability to use, this system or any of its components. Raven Industries shall not be held responsible for any modifications or repairs made outside our facilities, nor damages resulting from inadequate maintenance of this system.

As with all wireless and satellite signals, several factors may affect the availability and accuracy of wireless and satellite navigation and correction services (e.g. GPS, GNSS, SBAS, etc.). Therefore, Raven Industries cannot guarantee the accuracy, integrity, continuity, or availability of these services and cannot guarantee the ability to use Raven systems, or products used as components of systems, which rely upon the reception of these signals or availability of these services. Raven Industries accepts no responsibility for the use of any of these signals or services for other than the stated purpose.

Chapter 1	<i>Important Safety Information</i>	1
	Hydraulic Safety	2
	Electrical Safety	2
Chapter 2	<i>Introduction</i>	3
	Preparing for Installation	3
	Recommendations	4
	Point of Reference	4
	Updates	4
	Kit Contents	5
Chapter 3	<i>Hydraulic System Installation</i>	9
	Install Fittings in the SmarTrax Valve	10
	Mount the SmarTrax Valve	11
	Disconnect the Machine's Existing Hoses	12
	Install the Load Sense Hose	12
	Install the Left and Right Steering Hoses	14
	Install the Pressure and Tank Hoses	15
	Hydraulic Diagram	17
Chapter 4	<i>Cab Component Installation</i>	19
	Install the Node Harness	19
	Install the SmarTrax Node	21
	Mount the SmarTrax Node	21
	Node Mounting Locations	23
	Install the Foot Switch	24
	Install the Valve Harness	25
Chapter 5	<i>Startup Procedures</i>	27
	Verify the SmarTrax System Installation	27
	Calibrate the SmarTrax System	28

CHAPTER

1

Important Safety Information

NOTICE

Read this manual and the operation and safety instructions included with your implement and/or controller carefully before installing the SmarTrax™ system.

- Follow all safety information presented within this manual.
- If you require assistance with any portion of the installation or service of your Raven equipment, contact your local Raven dealer for support.
- Follow all safety labels affixed to the SmarTrax system components. Be sure to keep safety labels in good condition and replace any missing or damaged labels. To obtain replacements for missing or damaged safety labels, contact your local Raven dealer.

When operating the machine after installing SmarTrax, observe the following safety measures:

- Be alert and aware of surroundings.
- Do not operate SmarTrax or any agricultural equipment while under the influence of alcohol or an illegal substance.
- Remain in the operator's position in the machine at all times when SmarTrax is engaged.
- Disable SmarTrax when exiting the operator's seat and machine.
- Do not drive the machine with SmarTrax enabled on any public road.
- Determine and remain a safe working distance from other individuals. The operator is responsible for disabling SmarTrax when the safe working distance has diminished.
- Ensure SmarTrax is disabled prior to starting any maintenance work on SmarTrax or the machine.



WARNING

- When starting the machine for the first time after installing SmarTrax, be sure that all persons stand clear in case a hose has not been properly tightened.
- The machine must remain stationary and switched off during SmarTrax installation or maintenance.

 **CAUTION**

Hydraulic Safety

- Raven Industries recommends that appropriate protective equipment be worn at all times when working on the hydraulic system.
- Never attempt to open or work on a hydraulic system with the equipment running. Care should always be taken when opening a system that has been previously pressurized.
- When disconnecting the hydraulic hoses or purging is required, be aware that the hydraulic fluid may be extremely hot and under high pressure. Caution must be exercised.
- Any work performed on the hydraulic system must be done in accordance with the machine manufacturer's approved maintenance instructions.
- When installing SmarTrax hydraulics or performing diagnostics, maintenance, or routine service, ensure that precautions are taken to prevent any foreign material or contaminants from being introduced into the machine's hydraulic system. Objects or materials that are able to bypass the machine's hydraulic filtration system will reduce performance and possibly damage the SmarTrax valve.

Electrical Safety

- Always verify that the power leads are connected to the correct polarity as marked. Reversing the power leads could cause severe damage to the equipment.
- Ensure that the power cable is the last cable to be connected.

CHAPTER

2

Introduction

Congratulations on your purchase of the SmarTrax system! This system is designed to provide cutting-edge, hands-free steering of the machine via Global Positioning System (GPS) coordinates.

This manual applies to the following machines:

MAKE: AGCO RoGator

MODEL: RG900, RG1100, and RG1300

FIGURE 1. AGCO RoGator RG1100



Preparing for Installation

Before installing the SmarTrax system, park the machine where the ground is level, clean, and dry. Turn off the machine and leave it turned off for the duration of the installation process. Bleed pressure from the hydraulic system by loosening the hydraulic fittings slowly, where applicable.

During the installation process, follow good safety practices. Be sure to carefully read the instructions in this manual as you complete the installation process.

Recommendations

Raven Industries recommends the following best practices when installing or operating the SmarTrax system for the first time, at the start of the season, or when moving the SmarTrax system to another machine:

- Install the GPS antenna on the front center of the machine's cab.
- Ensure the machine's hydraulic filters have been recently changed and there are no issues with the machine's hydraulic system (e.g., pump issues, faulty hydraulic motors, fine metal deposits in the hydraulic hoses, etc.).
- Ensure the machine's hydraulic valve is using fresh oil and debris is flushed from the hydraulic hoses, valves, and filters.

Raven Industries recommends the following best practices when installing the SmarTrax system:

- Use part numbers to identify the parts.
- Do not remove the plastic wrap from a part until it is necessary for installation.
- Do not remove plastic caps from a part until it is necessary for installation.

Point of Reference

The instructions in this manual assume that you are standing behind the machine, looking toward the cab.

Updates

Software and manual updates are available on the Raven Applied Technology website:

<http://www.ravenhelp.com>

At Raven Industries, we strive to make your experience with our products as rewarding as possible. One way to improve this experience is to provide us with feedback on this manual.

Your feedback will help shape the future of our product documentation and the overall service we provide. We appreciate the opportunity to see ourselves as our customers see us and are eager to gather ideas on how we have been helping or how we can do better.

To serve you best, please send an email with the following information to

techwriting@ravenind.com

-RoGator RG900, RG1100, and RG1300 SmarTrax™ Installation Manual

-Manual No. 016-4001-090 Rev. B

-Any comments or feedback (include chapter or page numbers if applicable).

-Let us know how long have you been using this or other Raven products.

We will not share your email or any information you provide with anyone else. Your feedback is valued and extremely important to us.

Thank you for your time.

Kit Contents

This section contains a list of the components that are included in the SmarTrax kit. Before beginning the SmarTrax installation, compare the items in the kit with the components on this list. If you have questions about the kit, contact your Raven dealer.

Note: The SmarTrax node (P/N 063-0173-031) is sold separately. Contact your local Raven dealer for ordering information.

TABLE 1. SmarTrax Installation Kit (P/N 117-4001-090)

Picture	Item Description	Part Number	Qty.
Not Pictured	Manual - RoGator RG900-RG1300 SmarTrax Installation	016-4001-090	1
Not Pictured	Manual - SmarTrax and SmartSteer Calibration & Operation	016-0171-277	1
	Valve - SmarTrax Hydraulic	063-0131-129	1
	Bracket - Node Mounting	107-0172-146	1
	Bracket - Hydraulic Valve Mounting	107-0172-147	1
	Cable - Node Harness	115-2001-052	1
	Cable - Valve Harness	115-2001-053	1
	Assembly - Enable Foot Switch	063-0172-470	1

TABLE 1. SmarTrax Installation Kit (P/N 117-4001-090)

Picture	Item Description	Part Number	Qty.
	Transducer - 0-3000 PSI Pressure	422-0000-086	1
	Bolt - 5/16"-18 x 7/8" Hex	311-0052-104	4
	Bolt - 3/8"-16 UNC x 1" Hex	311-0054-105	3
	Bolt - 1/2"-13 UNC x 1" Hex	311-0058-095	2
	Bolt - M6 x 1.0 x 20 mm Hex	311-0070-010	2
	Nut - 1/2"-13 Zinc Flanged Lock	312-1001-166	2
	Nut - 3/8"-16 Nylon Insert Thin Lock	312-4001-109	3
	Washer - 1/4" Split Lock	313-1000-017	4
	Washer - 5/16" Split Lock	313-1000-019	4
	Washer - 1/2" Flat	313-2300-017	2

TABLE 2. SmarTrax Installation Kit (P/N 117-4001-090)

Picture	Item Description	Part Number	Qty.
	Fitting - -8 ORFS M/M/F Swivel Run Tee Adapter	333-0012-028	4
	Fitting - -6 ORFS (M) to -6 SAE O-Ring (M) Straight Adapter	333-0012-084	5
	Fitting - -4 ORFS (M) to -6 SAE O-Ring (M) Straight Adapter	333-0012-195	1
	Hydraulic Hose - -8 ORFS (F) 90° to -6 ORFS (F) - 55"	214-1000-921	3
	Hydraulic Hose - -8 ORFS (F) to -6 ORFS (F) - 55"	214-1000-922	1
	Hydraulic Hose - -6 ORFS (F) 90° to -4 ORFS (F) - 61"	214-1000-923	1

CHAPTER

3

***Hydraulic System
Installation***



! WARNING

Hydraulics are under pressure. Care should always be taken with a system that has been pressurized.

Before beginning the SmarTrax hydraulic installation, turn off the machine and relieve pressure by turning the steering wheel left and right.

Never work on a hot machine. Always allow it to cool before performing diagnostics, maintenance, or routine service.

When disconnecting or purging hydraulic hoses, be aware that the hydraulic fluid within the machine's system may be extremely hot and under high pressure.

Tampering with hydraulic valves may cause serious injury or death, and will void the warranty.



! CAUTION

When installing SmarTrax hydraulic or performing diagnostics, maintenance, or routine service, ensure precautions are taken to prevent any foreign material from being introduced into the machine's hydraulic system.


Objects or materials that are able to bypass the machine's hydraulic filtration system will reduce performance and possibly damage the SmarTrax hydraulic valve.

	NOTICE
<p>The appearance of the SmarTrax hydraulic valve may vary slightly from the images contained in this manual. However, the fittings, hose connections, and cable connections remain the same.</p>	

Install Fittings in the SmarTrax Valve

Before mounting the SmarTrax valve (P/N 063-0131-129) on the machine, install the proper fittings in the valve. This prepares the valve for installation and simplifies the hose connection process later in the procedure.

FIGURE 1. Fittings Installed in the SmarTrax Valve



Fitting	Part Number	Port
Fitting - -6 ORFS (M) to -6 SAE O-Ring (M) Straight Adapter	333-0012-084	A, B P, T LS STEER
Fitting - -4 ORFS (M) to -6 SAE O-Ring (M) Straight Adapter	333-0012-195	LSPV
Transducer - 0-3000 PSI Pressure	422-0000-086	PS

Mount the SmarTrax Valve


FIGURE 2. SmarTrax Valve Mounting Location



Note: Some models may have pre-drilled holes in the center cross-member of the machine. If pre-drilled holes are not present, use a 5/16" drill bit to drill holes in the location illustrated in Figure 2 above.

1. Mount the valve mounting bracket (P/N 107-0172-147) to the center cross-member of the machine using two 1/2"-13 UNC x 1" hex bolts (P/N 311-0058-095), two 1/2" flat washers (P/N 313-2300-017), and two 1/2"-13 zinc flanged lock nuts (P/N 312-1001-166).

FIGURE 3. SmarTrax Valve Mounted to the Machine



2. Install the SmarTrax valve (P/N 063-0131-129) on the valve mounting bracket (P/N 063-0131-129) using four 5/16"-18 x 7/8" hex bolts (P/N 311-0052-104) and four 5/16" split lock washers (P/N 313-1000-019).


Disconnect the Machine's Existing Hoses

FIGURE 4. Steering Orbital Location



1. Locate the steering orbital in front of the cab.

FIGURE 5. Machine's Hoses Disconnected from Steering Orbital



2. Label the machine's existing hoses with the corresponding port.

Note: It may be necessary to trace the lines to the steering cylinders, hydraulic pump, and tank to determine the correct labeling of the hoses.

3. Disconnect the machine's hoses from the steering orbital.

Install the Load Sense Hose


1. Route the machine's existing load sense hose to the SmarTrax valve (P/N 063-0131-129).
2. Connect the load sense hose to the fitting installed in Port LSPV of the SmarTrax valve.

FIGURE 6. Load Sense Hose Installed on Steering Orbital



3. Install the straight end of the supplied hydraulic hose (P/N 214-1000-923) on the load sense port of the steering orbital.

FIGURE 7. Load Sense Hose Installed on SmarTrax Valve



4. Connect the 90° end of the installed hydraulic hose to the fitting installed in Port LS STEER of the SmarTrax valve.




Install the Left and Right Steering Hoses

FIGURE 8. Left and Right Ports on Steering Orbital




1. Locate the left and right steering ports on the machine's steering orbital.

FIGURE 9. Tee Adapter Fittings Installed



2. Install -8 ORFS M/M/F swivel run tee adapter fittings (P/N 333-0012-028) in the left and right steering ports of the steering orbital.
3. Connect the machine's left steering hose to the straight end of the tee fitting installed in the left steering port.
4. Connect the machine's right steering hose to the straight end of the tee fitting installed in the right steering port.

FIGURE 10. Left and Right Steering Hoses Installed



5. Install the 90° end of the supplied hydraulic hose (P/N 214-1000-921) on the 90° end of the tee fitting installed in the left steering port of the steering orbital.
6. Connect the straight end of the installed hydraulic hose to the fitting installed in Port A of the SmarTrax valve.
7. Install the 90° end of the supplied hydraulic hose (P/N 214-1000-921) on the 90° end of the tee fitting installed in the right steering port of the steering orbital.
8. Connect the straight end of the installed hydraulic hose to the fitting installed in Port B of the SmarTrax valve.

Install the Pressure and Tank Hoses

FIGURE 11. Pressure and Tank Hoses Installed on Steering Orbital




9. Install -8 ORFS M/M/F swivel run tee fittings (P/N 333-0012-028) in the pressure and tank ports of the machine's steering orbital.
10. Connect the machine's pressure hose to the straight end of the tee fitting installed in the pressure port.
11. Install the 90° end of the supplied hydraulic hose (P/N 214-1000-921) on the 90° end of the installed tee fitting.


12. Connect the straight end of the installed hydraulic hose to the fitting installed in Port P of the SmarTrax valve.
13. Connect the machine's tank hose to the straight end of the tee fitting installed in the tank port.
14. Install the -8 ORFS end of the supplied hydraulic hose (P/N 214-10000-922) on the 90° end of the installed tee fitting.
15. Connect the -6 ORFS end of the installed hydraulic hose to the fitting installed in Port T of the SmarTrax valve.

Hydraulic Diagram

Before SmarTrax Installation



After SmarTrax Installation



CHAPTER


4

Cab Component Installation

Install the Node Harness


1. Remove the access panel cover on the outside right-rear corner of the cab.

FIGURE 1. Node Harness Routed into Cab



2. Route the two large, rectangular connectors of the node harness (P/N 115-2001-052) into the machine's cab through the access hole.
3. Remove the bulkhead plug from the cab floor in the right-rear corner of the cab.

FIGURE 2. STRAX BLKHD Connection




4. Install the STRAX BLKHD connector in the hole.

FIGURE 3. CAB HARNESS Connection



5. Connect the CAB HARNESS connector into the machine's mating bulkhead connector.

FIGURE 4. DGPS and DGPS OUT Connections



6. Connect the DGPS OUT connector of the node harness to the DGPS connector on the console cable.

7. Connect the DGPS connector to the receiver or other GPS source.

FIGURE 5. Ring Terminals Connected



8. Install the ring terminal connections on the appropriate power terminal studs.

Install the SmarTrax Node

Note: The SmarTrax node (P/N 063-0173-031) is sold separately. Contact your local Raven dealer for ordering information.

Mount the SmarTrax Node

FIGURE 6. Node Mounted to Mounting Plate



1. Mount the node (P/N 063-0173-031) to the node mounting bracket (P/N 107-0172-146) using three 3/8" 16 UNC x 1" hex bolts (P/N 311-0054-105) and three 3/8"-16 nylon insert thin lock nuts (P/N 312-4001-109).


FIGURE 7. SmarTrax Node Installed



2. Mount the node mounting plate to the standoffs on the panel to the right of the operator's seat using two M6 x 1.0 x 20 mm hex bolts (P/N P/N 311-0070-010) and two M6 split lock washers (P/N 313-1000-017).

Note: *The mounting plate should be oriented so that the node connectors point toward the front of the machine.*


FIGURE 8. Node Harness Connected to Node



3. Connect the node connectors from the node harness (P/N 115-2001-052) into the correct ports of the SmarTrax node.
4. Tighten the bolts on the node connectors to secure the connections.

Node Mounting Locations

FIGURE 9. Node Mounting



When choosing the location for the SmarTrax node, consider the following points:

- Mount the SmarTrax node inside the machine's cab on a flat, level surface for proper performance and cable connection.
- One of the six numbered direction arrows on the node must be oriented in the direction of forward vehicle travel, one arrow pointing straight up, and two of the arrows parallel to the ground.

Note: Make a note of the number of the arrow that is oriented in the direction of forward vehicle travel. This number will be needed during the SmarTrax calibration process.

- The node mounting location must not create tripping hazards.
- Mount the node in a location where it will not be kicked or jarred during normal equipment operation.
- The location must allow cable routing to avoid crimping or damaging the cables or the node connections.
- Securely fasten the node using bolts or screws through at least two of the three mounting holes. When mounted properly, the node should not become loose or rotate.

Install the Foot Switch

FIGURE 10. Foot Switch Installed




1. Select a suitable location for the foot switch (P/N 063-0172-470) to be installed.

Note: *The foot switch should be installed in a location where the operator has easy access to it and is able to fully press the pedal.*


2. Using the holes in the foot switch as a template, drill holes in the floor of the cab.
3. Secure the foot switch to the floor by installing the supplied screws in each of the mounting holes.
4. Lift the floor mat and locate the access panel in the floor of the cab.

FIGURE 11. Foot Switch Cable Connected Routed



5. Remove the access plate.
6. Route the foot switch cable connector along the machine's existing cables and toward the rear of the cab.

FIGURE 12. Foot Switch Cable Connection




7. Connect the foot switch cable connector to the REMOTE ENGAGE SW connector on the machine's harness.
8. Replace the access plate and floor mat.

Install the Valve Harness

1. Connect the PSI 1 connector of the valve harness (P/N 115-2001-053) to the transducer (P/N 422-0000-086) installed in Port PS of the SmarTrax valve (P/N 063-0131-129).
2. Connect the DB 1, PORT 1A connector to Port 1A of the SmarTrax valve.
3. Connect the DB 2, PORT 1B connector to Port 1B of the SmarTrax valve.
4. Connect the RIGHT, PORT 2-TOP connector to the top coil of the stack on the SmarTrax valve.
5. Connect the LEFT, PORT 2-BOTTOM connector to the bottom coil of the stack on the SmarTrax valve.
6. Connect the 12-pin Deutsch connector of the valve harness to the mating STRAX BLKHD connector of the node harness (P/N 115-2001-052) installed at the machine's bulkhead earlier in the procedure.



FIGURE 13. Valve Harness Wiring Diagram



CHAPTER

5

Startup Procedures



WARNING

When starting the machine for the first time after installing SmarTrax, be sure that all persons stand clear in case a hose has not been properly tightened.



WARNING

Do not use hands to check for leaks. Hydraulic fluid under pressure can penetrate the skin and cause serious injury or death.

Verify the SmarTrax System Installation

1. Turn on the machine.
2. Double-check all fitting and hose connections to ensure that:
 - Hoses are not rubbing on or interfering with moving parts.
 - Hydraulic fluid is not leaking from the system.
3. Turn the machine's wheels fully from side to side repeatedly to remove air from the hydraulic system.

Note: *During the SmarTrax system installation, whenever the hydraulic system is purged for maintenance, or when fittings are loosened or disconnected, air is introduced into the lines of the hydraulic system. If air pockets are present, the wheels may not move consistently when the steering wheel is turned.*

4. Continue turning the wheels until they move steadily and smoothly when the steering wheel is turned.

5. Access the System Diagnostic screen by selecting the MACHINE TEST option on the Machine Type screen and turn the wheels using the Raven console.

Note: *If there are issues with the SmarTrax system, turn off the machine and correct them immediately. For additional assistance, refer to the SmarTrax and SmartSteer Calibration & Operation Manual (P/N 016-0171-277) or contact your local Raven dealer.*

Calibrate the SmarTrax System

Refer to the SmarTrax & SmartSteer Calibration and Operation Manual (P/N 016-0171-277) for instructions on calibrating the SmarTrax system, adjusting system settings, and system operation.

C**Cab Component Installation**

- Installing the Foot Switch 24
- Installing the Node Harness 19
- Installing the SmarTrax Node 21
 - Mounting the Node 21
 - Node Mounting Locations 23
- Installing the Valve Harness 25

H**Hydraulic Installation**

- Disconnecting the Machine's Existing Hoses 12
- Hydraulic Diagram 17
- Installing Fittings in the SmarTrax Valve 10
- Installing the Left and Right Steering Hoses 14
- Installing the Load Sense Hose 12
- Installing the Pressure and Tank Hoses 15
- Mounting the SmarTrax Valve 11

I**Important Safety Information**

- Electrical Safety 2
- Hydraulic Safety 2

Introduction

- Kit Contents 5
- Preparing for Installation 3
 - Point of Reference 4
 - Recommendations 4

K**Kit Contents 5****S****Startup Procedures**

- Calibrating the SmarTrax System 28
- Verifying the SmarTrax System Installation 27

RAVEN

Limited Warranty

What Does this Warranty Cover?

This warranty covers all defects in workmanship or materials in your Raven Applied Technology Division product under normal use, maintenance, and service when used for intended purpose.

How Long is the Coverage Period?

Raven Applied Technology products are covered by this warranty for 12 months from the date of retail sale. In no case will the Limited Warranty period exceed 24 months from the date the product was issued by Raven Industries Applied Technology Division. This warranty coverage applies only to the original owner and is non-transferable.

How Can I Get Service?

Bring the defective part and proof of purchase to your Raven dealer. If the dealer approves the warranty claim, the dealer will process the claim and send it to Raven Industries for final approval. The freight cost to Raven Industries will be the customer's responsibility. The Return Materials Authorization (RMA) number must appear on the box and all documentation (including proof of purchase) must be included inside the box to be sent to Raven Industries.

What Will Raven Industries Do?

Upon confirmation of the warranty claim, Raven Industries will (at our discretion) repair or replace the defective product and pay for the standard return freight, regardless of the inbound shipping method. Expedited freight is available at the customer's expense.

What is not Covered by this Warranty?

Raven Industries will not assume any expense or liability for repairs made outside our facilities without written consent. Raven Industries is not responsible for damage to any associated equipment or products and will not be liable for loss of profit, labor, or other damages. The obligation of this warranty is in lieu of all other warranties, expressed or implied, and no person or organization is authorized to assume any liability for Raven Industries.

Damages caused by normal wear and tear, misuse, abuse, neglect, accident, or improper installation and maintenance are not covered by this warranty.



Extended Warranty

What Does this Warranty Cover?

This warranty covers all defects in workmanship or materials in your Raven Applied Technology Division product under normal use, maintenance, and service when used for intended purpose.

Do I Need to Register My Product to Qualify for the Extended Warranty?

Yes. Products/systems must be registered within 30 days of retail sale to receive coverage under the Extended Warranty. If the component does not have a serial tag, the kit it came in must be registered instead.

Where Can I Register My Product for the Extended Warranty?

To register, go online to www.ravenhelp.com and select Product Registration.

How Long is the Extended Warranty Coverage Period?

Raven Applied Technology products that have been registered online are covered for an additional 12 months beyond the Limited Warranty for a total coverage period of 24 months from the date of retail sale. In no case will the Extended Warranty period exceed 36 months from the date the product was issued by Raven Industries Applied Technology Division. This Extended Warranty coverage applies only to the original owner and is non-transferable.

How Can I Get Service?

Bring the defective part and proof of purchase to your Raven dealer. If the dealer approves the warranty claim, the dealer will process the claim and send it to Raven Industries for final approval. The freight cost to Raven Industries will be the customer's responsibility. The Return Materials Authorization (RMA) number must appear on the box and all documentation (including proof of purchase) must be included inside the box to be sent to Raven Industries. In addition, the words "Extended Warranty" must appear on the box and all documentation if the failure is between 12 and 24 months from the retail sale.

What Will Raven Industries Do?

Upon confirmation of the product's registration for the Extended Warranty and the claim itself, Raven Industries will (at our discretion) repair or replace the defective product and pay for the standard return freight, regardless of the inbound shipping method. Expedited freight is available at the customer's expense.

What is Not Covered by the Extended Warranty?

Raven Industries will not assume any expense or liability for repairs made outside our facilities without written consent. Raven Industries is not responsible for damage to any associated equipment or products and will not be liable for loss of profit, labor, or other damages. Cables, hoses, software enhancements, and remanufactured items are not covered by this Extended Warranty. The obligation of this warranty is in lieu of all other warranties, expressed or implied, and no person or organization is authorized to assume any liability for Raven Industries.

Damages caused by normal wear and tear, misuse, abuse, neglect, accident, or improper installation and maintenance are not covered by this warranty.