

**Case IH Patriot 4420 - Steering Ready
(2009 & Newer)
SmarTrax™ Installation Manual**

P/N 016-5032-015 Rev C 04/16 E21372

Chapter 1	<i>Important Safety Information</i>	1
	Hydraulic Safety	2
	Electrical Safety	2
Chapter 2	<i>Introduction</i>	3
	Preparing for Installation	3
	Recommendations	4
	Point of Reference	4
	Updates	4
	Kit Contents	5
	Case IH Patriot 4420 without Phoenix 200 Antenna	5
	Case IH Patriot 4420 with Phoenix 200 Antenna	6
Chapter 3	<i>Cab Component Installation</i>	9
	Prepare for Installation	9
	Install the Case Interface Box	10
	Install the SmarTrax Node	11
	Mount the SmarTrax Node	11
	Node Mounting Locations	14
	Install the Phoenix 200 Antenna (If Applicable)	15
	Complete the SmarTrax System Installation	15
	Calibrate the SmarTrax System	16
	Enable Switch	16
	System Diagrams	17

CHAPTER

1

Important Safety Information

NOTICE

Read this manual and the operation and safety instructions included with your implement and/or controller carefully before installing the SmarTrax™ system.

- Follow all safety information presented within this manual.
- If you require assistance with any portion of the installation or service of your Raven equipment, contact your local Raven dealer for support.
- Follow all safety labels affixed to the SmarTrax system components. Be sure to keep safety labels in good condition and replace any missing or damaged labels. To obtain replacements for missing or damaged safety labels, contact your local Raven dealer.

When operating the machine after installing SmarTrax, observe the following safety measures:

- Be alert and aware of surroundings.
- Do not operate SmarTrax or any agricultural equipment while under the influence of alcohol or an illegal substance.
- Remain in the operator's position in the machine at all times when SmarTrax is engaged.
- Disable SmarTrax when exiting the operator's seat and machine.
- Do not drive the machine with SmarTrax enabled on any public road.
- Determine and remain a safe working distance from other individuals. The operator is responsible for disabling SmarTrax when the safe working distance has diminished.
- Ensure SmarTrax is disabled prior to starting any maintenance work on SmarTrax or the machine.



WARNING

- When starting the machine for the first time after installing SmarTrax, be sure that all persons stand clear in case a hose has not been properly tightened.
- The machine must remain stationary and switched off during SmarTrax installation or maintenance.

 **CAUTION**

Hydraulic Safety

- Raven Industries recommends that appropriate protective equipment be worn at all times when working on the hydraulic system.
- Never attempt to open or work on a hydraulic system with the equipment running. Care should always be taken when opening a system that has been previously pressurized.
- When disconnecting the hydraulic hoses or purging is required, be aware that the hydraulic fluid may be extremely hot and under high pressure. Caution must be exercised.
- Any work performed on the hydraulic system must be done in accordance with the machine manufacturer's approved maintenance instructions.
- When installing SmarTrax hydraulics or performing diagnostics, maintenance, or routine service, ensure that precautions are taken to prevent any foreign material or contaminants from being introduced into the machine's hydraulic system. Objects or materials that are able to bypass the machine's hydraulic filtration system will reduce performance and possibly damage the SmarTrax valve.

Electrical Safety

- Always verify that the power leads are connected to the correct polarity as marked. Reversing the power leads could cause severe damage to the equipment.
- Ensure that the power cable is the last cable to be connected.

CHAPTER

2

Introduction

Congratulations on your purchase of the SmarTrax system! This system is designed to provide cutting-edge, hands-free steering of the machine via Global Positioning System (GPS) coordinates.

This manual applies to the following machines:

MAKE: Case IH
MODEL: 4420 - Steering Ready
YEAR: 2009 and Newer

FIGURE 1. Case IH Patriot



Preparing for Installation

Before installing the SmarTrax system, park the machine where the ground is level, clean, and dry. Turn off the machine and leave it turned off for the duration of the installation process. Bleed pressure from the hydraulic system by loosening the hydraulic fittings slowly, where applicable.

During the installation process, follow good safety practices. Be sure to carefully read the instructions in this manual as you complete the installation process.

Recommendations

Raven Industries recommends the following best practices when installing or operating the SmarTrax system for the first time, at the start of the season, or when moving the SmarTrax system to another machine:

- Install the GPS antenna in the recommended location. Refer to the following table for the machine-specific antenna mounting location.

Note: *If your machine is not listed, install the antenna on the front-center of the cab.*

Note: *The units in the table below are measured in inches. To convert the values to centimeters, multiply the listed value by 2.54.*

Machine Preset	Antenna X Position (left to right)	Antenna Y Position (front to back in inches)	Antenna Z Position (ground to top of antenna in inches)
CaseIH SPX 33/44x0 120'	Centered	174	144
CaseIH SPX 4260/44x0	Centered	174	144

- Ensure the machine's hydraulic filters have been recently changed and there are no issues with the machine's hydraulic system (e.g., pump issues, faulty hydraulic motors, fine metal deposits in the hydraulic hoses, etc.).
- Ensure the machine's hydraulic system is using fresh oil and debris is flushed from the hydraulic hoses, valves, and filters.

Raven Industries recommends the following best practices when installing the SmarTrax system:

- Use part numbers to identify the parts.
- Do not remove the plastic wrap from a part until it is necessary for installation.
- Do not remove plastic caps from a part until it is necessary for installation.

Point of Reference

The instructions in this manual assume that you are standing behind the machine, looking toward the cab.

Updates

Software and manual updates are available on the Raven Applied Technology website:

<http://www.ravenhelp.com>

At Raven Industries, we strive to make your experience with our products as rewarding as possible. One way to improve this experience is to provide us with feedback on this manual.

Your feedback will help shape the future of our product documentation and the overall service we provide. We appreciate the opportunity to see ourselves as our customers see us and are eager to gather ideas on how we have been helping or how we can do better.

To serve you best, please send an email with the following information to

techwriting@ravenind.com

-Case IH Patriot 4420 - Steering Ready (2009 & Newer) SmarTrax™ Installation Manual

-Manual No. 016-5032-015 Rev. C

-Any comments or feedback (include chapter or page numbers if applicable).

-Let us know how long have you been using this or other Raven products.

We will not share your email or any information you provide with anyone else. Your feedback is valued and extremely important to us.

Thank you for your time.

Kit Contents

This section contains a list of the components that are included in the SmarTrax kit. Before beginning the SmarTrax installation, compare the items in the kit with the components on this list. If you have questions about the kit, contact your Raven dealer.

Case IH Patriot 4420 without Phoenix 200 Antenna

TABLE 1. SmarTrax Installation Kit (P/N 117-5032-015)

Picture	Item Description	Part Number	Qty.
Not Pictured	Manual - Case IH Patriot 4420 (Model Year 2009-2011) - Steering Ready SmarTrax Installation	016-5032-015	1
Not Pictured	Manual - SmarTrax and SmartSteer Calibration & Operation	016-0171-277	1
	Box - Case IH Interface	063-0173-038	1

TABLE 1. SmarTrax Installation Kit (P/N 117-5032-015)

Picture	Item Description	Part Number	Qty.
	Node - SmarTrax RTK	063-0173-228	1
	Bracket - Node Mounting	107-0172-084	1
	Cable - Node Harness	115-4001-127	1
	Cable - 4' CAN Extension	115-4001-150	1
	Nut - 3/8"-16 Zinc Flanged Lock	312-1001-164	3
	Nut - M6 Lock	312-4000-207	4
	Washer - 0.25" ID x 0.562" OD	313-2300-009	4

Case IH Patriot 4420 with Phoenix 200 Antenna

TABLE 2. SmarTrax Installation Kit (P/N 117-5032-016)

Picture	Item Description	Part Number	Qty.
Not Pictured	Manual - Case IH Patriot 4420 (Model Year 2009-2011) - Steering Ready SmarTrax Installation	016-5032-015	1
Not Pictured	Manual - SmarTrax and SmartSteer Calibration & Operation	016-0171-277	1

TABLE 2. SmarTrax Installation Kit (P/N 117-5032-016)

Picture	Item Description	Part Number	Qty.
	Box - Case IH Interface	063-0173-038	1
	Node - SmarTrax RTK	063-0173-228	1
	Bracket - Node Mounting	107-0172-084	1
	Receiver - Phoenix 200 Helix	063-0172-719	1
	Cable - P200 to Node Harness	115-4001-027	1
	Cable - Node Harness	115-4001-127	1
	Cable - 4' CAN Extension	115-4001-150	1
	Nut - 3/8"-16 Zinc Flanged Lock	312-1001-164	3
	Nut - M6 Lock	312-4000-207	4
	Washer - 0.25" ID x 0.562" OD	313-2300-009	4

CHAPTER

3

Cab Component Installation

Prepare for Installation

FIGURE 1. SmarTrax Node Mounting Location




1. Identify the SmarTrax node mounting location under the instructional seat.
2. Flip up the seat cushion of the instructional seat and remove the storage tub.

FIGURE 2. Bolts to be Removed



3. Remove the eight bolts used to secure the back panel.

FIGURE 3. Back Panel Removed




4. Remove the back panel to allow for easier cable routing.
5. If applicable, temporarily remove the fan assembly.

Install the Case Interface Box


1. Locate the Case steering control system cables under the instructional seat.

FIGURE 4. Case Cable Connected to the Case Interface Box



2. Connect the Case steering control cables to the Case interface box (P/N 063-0173-038).
3. Connect the round, 37-pin connector of the node harness (P/N 115-4001-127) to the 37-pin port of the Case interface box.

FIGURE 5. Double-Sided Tape on Case IH Interface Box



4. Remove the backing from the double-sided tape.
5. Adhere the Case interface box to the wall of the instructional seat compartment, away from the node mounting standoffs located on the floor of the compartment.

Note: Ensure the Case interface box will not interfere with the storage tub when it is reinstalled.

Install the SmarTrax Node

Mount the SmarTrax Node

FIGURE 6. SmarTrax Node Installed




1. Mount the SmarTrax node to the node mounting bracket (P/N 107-0172-084) using three 3/8"-16 nylon insert lock nuts (P/N 312-1001-164).

2. Install the two large, rectangular connectors of the node harness (P/N 115-4001-127) into the correct ports of the node.
3. Tighten the bolts on the harness connectors to secure the connections.
4. Place the node mounting bracket in the instructional seat compartment, aligning the holes in the mounting bracket with the existing mounting studs.

Note: *The node connectors should be pointing toward the operator's seat.*



5. Secure the node mounting bracket to the floor using four 1/4" flat washers (P/N 313-2300-009) and four M6 lock nuts (P/N 312-4000-207).

FIGURE 7. Node Harness Routing Location



6. Route the remaining node harness through the instructional seat access hole and around the back of the operator's seat.

FIGURE 8. CAN Connector Installed on Machine's DIAGNOSTIC Connector



7. Connect the CAN extension cable (P/N 115-4001-150) to the machine's existing DIAGNOSTIC connector bolted to the fuse panel as shown in Figure 8.


8. Route the opposite end of the cable out the fuse panel and around the back of the operator's seat to the instructional seat compartment.
9. Connect the CAN connector to the CAN connection on the node harness.

FIGURE 9. DGPS OUT Connector Routed Under Operator's Seat



10. Route the DGPS OUT connector out the right corner of the operator's seat base and under the right arm rest.


FIGURE 10. DGPS OUT Connected to Console Receiver Connection



11. Route and connect the DGPS OUT connector to the console's DGPS connector.

Node Mounting Locations

FIGURE 11. Node Mounting



When choosing the location for the SmarTrax node, consider the following points:

- Mount the SmarTrax node inside the machine's cab on a flat, level surface for proper performance and cable connection.
- One of the six numbered direction arrows on the node must be oriented in the direction of forward vehicle travel, one arrow pointing straight up, and two of the arrows parallel to the ground.

Note: *Make a note of the number of the arrow that is oriented in the direction of forward vehicle travel. This number will be needed during the SmarTrax calibration process.*

- The node mounting location must not create tripping hazards.
- Mount the node in a location where it will not be kicked or jarred during normal equipment operation.
- The location must allow cable routing to avoid crimping or damaging the cables or the node connections.
- Securely fasten the node using bolts or screws through at least two of the three mounting holes. When mounted properly, the node should not become loose or rotate.


Install the Phoenix 200 Antenna (If Applicable)

FIGURE 12. Phoenix 200 Antenna Installed



1. Install the Phoenix 200 antenna (P/N 063-0172-719) on the existing mounting plate on the cab roof.

FIGURE 13. GPS Connections



2. Connect the Phoenix 200 to Case harness cable (P/N 115-4001-027) between the antenna and the GPS roof connection.
3. Connect the CASE GPS connection and the DGPS IN connection from the node harness (P/N 115-4001-127) cable together.

Complete the SmarTrax System Installation

1. Reinstall the back panel of the instructional seat compartment.
2. Reinstall the fan assembly.
3. Replace the storage tub.

Calibrate the SmarTrax System

Refer to the SmarTrax and SmartSteer Calibration & Operation Manual (P/N 016-0171-277) for instructions on calibrating the SmarTrax system, adjusting system settings, and system operation.

Enable Switch


FIGURE 14. Enable Switch.




A factory-installed switch is installed on the floor of the machine's cab. Use this enable switch to engage and disengage the SmarTrax system after installation and calibration of the system is complete.

System Diagrams

ENVIZIO PRO/VIPER PRO CAN SMARTRAX CASE 4420 STEER-READY W/PHOENIX 200



ENVIZIO PRO/VIPER PRO CAN SMARTRAX CASE 4420 STEER-READY W/PHOENIX 300



C**Cab Component Installation** 9

- Calibrating the SmarTrax System 16
- Enable Switch 16
- Install the Phoenix 200 Antenna 15
- Installing the Case Interface Box 10
- Installing the SmarTrax Node 11
 - Mounting the SmarTrax Node 11
 - Node Mounting Locations 12, 14
- Preparing for Installation 9
- System Diagrams 17

I**Important Safety Information**

- Electrical Safety 2
- Hydraulic Safety 2

Introduction

- Kit Contents 5
 - Case IH Patriot with Phoenix 200 Antenna 6
 - Case IH Patriot without Phoenix 200 Antenna 5
- Preparing for Installation 3
 - Point of Reference 4
 - Recommendations 4

K**Kit Contents** 5

RAVEN

Limited Warranty

What Does this Warranty Cover?

This warranty covers all defects in workmanship or materials in your Raven Applied Technology Division product under normal use, maintenance, and service when used for intended purpose.

How Long is the Coverage Period?

Raven Applied Technology products are covered by this warranty for 12 months from the date of retail sale. In no case will the Limited Warranty period exceed 24 months from the date the product was issued by Raven Industries Applied Technology Division. This warranty coverage applies only to the original owner and is non-transferable.

How Can I Get Service?

Bring the defective part and proof of purchase to your Raven dealer. If the dealer approves the warranty claim, the dealer will process the claim and send it to Raven Industries for final approval. The freight cost to Raven Industries will be the customer's responsibility. The Return Materials Authorization (RMA) number must appear on the box and all documentation (including proof of purchase) must be included inside the box to be sent to Raven Industries.

What Will Raven Industries Do?

Upon confirmation of the warranty claim, Raven Industries will (at our discretion) repair or replace the defective product and pay for the standard return freight, regardless of the inbound shipping method. Expedited freight is available at the customer's expense.

What is not Covered by this Warranty?

Raven Industries will not assume any expense or liability for repairs made outside our facilities without written consent. Raven Industries is not responsible for damage to any associated equipment or products and will not be liable for loss of profit, labor, or other damages. The obligation of this warranty is in lieu of all other warranties, expressed or implied, and no person or organization is authorized to assume any liability for Raven Industries.

Damages caused by normal wear and tear, misuse, abuse, neglect, accident, or improper installation and maintenance are not covered by this warranty.



Extended Warranty

What Does this Warranty Cover?

This warranty covers all defects in workmanship or materials in your Raven Applied Technology Division product under normal use, maintenance, and service when used for intended purpose.

Do I Need to Register My Product to Qualify for the Extended Warranty?

Yes. Products/systems must be registered within 30 days of retail sale to receive coverage under the Extended Warranty. If the component does not have a serial tag, the kit it came in must be registered instead.

Where Can I Register My Product for the Extended Warranty?

To register, go online to www.ravenhelp.com and select Product Registration.

How Long is the Extended Warranty Coverage Period?

Raven Applied Technology products that have been registered online are covered for an additional 12 months beyond the Limited Warranty for a total coverage period of 24 months from the date of retail sale. In no case will the Extended Warranty period exceed 36 months from the date the product was issued by Raven Industries Applied Technology Division. This Extended Warranty coverage applies only to the original owner and is non-transferable.

How Can I Get Service?

Bring the defective part and proof of purchase to your Raven dealer. If the dealer approves the warranty claim, the dealer will process the claim and send it to Raven Industries for final approval. The freight cost to Raven Industries will be the customer's responsibility. The Return Materials Authorization (RMA) number must appear on the box and all documentation (including proof of purchase) must be included inside the box to be sent to Raven Industries. In addition, the words "Extended Warranty" must appear on the box and all documentation if the failure is between 12 and 24 months from the retail sale.

What Will Raven Industries Do?

Upon confirmation of the product's registration for the Extended Warranty and the claim itself, Raven Industries will (at our discretion) repair or replace the defective product and pay for the standard return freight, regardless of the inbound shipping method. Expedited freight is available at the customer's expense.

What is Not Covered by the Extended Warranty?

Raven Industries will not assume any expense or liability for repairs made outside our facilities without written consent. Raven Industries is not responsible for damage to any associated equipment or products and will not be liable for loss of profit, labor, or other damages. Cables, hoses, software enhancements, and remanufactured items are not covered by this Extended Warranty. The obligation of this warranty is in lieu of all other warranties, expressed or implied, and no person or organization is authorized to assume any liability for Raven Industries.

Damages caused by normal wear and tear, misuse, abuse, neglect, accident, or improper installation and maintenance are not covered by this warranty.